

**AD-A277 259**



2

**DODPOPHM/USA/DOD/NADTR93003 REVISION A**

**Superseding**

**DODPOPHM/USA/DOD/NADTR93003**

**April 1993**

**PERFORMANCE ORIENTED PACKAGING TESTING  
OF  
CONTAINER, SHIPPING AND STORAGE,  
MK 37 MOD 0, MK 287 MODS 0, 1, AND MK 764 MOD 0  
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

**Author:  
Peter W. Guppenberger  
Mechanical Engineer**

**DTIC  
ELECTE  
MAR 22 1994  
S E D**

**Performing Activity:  
Packaging, Handling, Storage and Transportability Center  
Naval Weapons Station Earle  
Colts Neck, New Jersey 07722-5023**

**March 1994**

**FINAL**

**DISTRIBUTION UNLIMITED**

**Sponsoring Organization:  
Commander, Naval Air Systems Command (AIR-4101L5)  
Department of the Navy  
Washington, DC 20361-8050**

**94-08961**

**94 3 21 0 27**

**DTIC QUALITY INSPECTED 1**

REPORT DOCUMENTATION PAGE		Form Approved OMB No 0704-0188	
Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 03/94	3. REPORT TYPE AND DATES COVERED POP Test (03/93)	
4. TITLE AND SUBTITLE  Performance Oriented Packaging Testing of Container, Shipping and Storage, Mk 37 Mod 0, Mk 287 Mods 0, 1 and Mk 764 Mod 0, for Packing Group II Solid Hazardous Materials		5. FUNDING NUMBERS	
6. AUTHOR(S) Peter W. Guppenberger			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  Packaging, Handling, Storage and Transportability Center Naval Weapons Station Earle Colts Neck, NJ 07722-5023		8. PERFORMING ORGANIZATION REPORT NUMBER  DODPOPHM/USA/DOD/NADTR93003 REVISION A	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  Commander, Naval Air Systems Command (AIR-4101L5) Department of the Navy Washington, DC 20361-8050		10. SPONSORING/MONITORING AGENCY REPORT NUMBER  Same as above	
11. SUPPLEMENTARY NOTES  N/A			
12a. DISTRIBUTION/AVAILABILITY STATEMENT		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Mk 37 Mod 0 Shipping and Storage Container (LD 269069) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was a simulated SIDEWINDER Rocket Motor weighing 46 kg (100 pounds)). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 2 kg (4 pounds) were added. Gross weight of the loaded container was 63 kg (137 pounds). The test results indicate that the container has conformed to the POP requirements.  In addition, due to their similarities in design, size and weight, this test is considered representative of qualification testing for the Mk 287 Mods 0, 1 (Drawing #1516486) and Mk 764 Mod 0 (Drawing #5972149) Shipping and Storage Containers as per the variation in Title 49 CFR 107, Sec. 178.601g(4), Variation 4.			
14. SUBJECT TERMS  POP Test of Mk 37 Mod 0, Mk 287 Mods 0, 1, and Mk 764 Mod 0 Shipping and Storage Container		15. NUMBER OF PAGES 7	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT  UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE  UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT  UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL

## INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 37 Mod 0 Shipping and Storage Container (LD 269069) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was a simulated SIDEWINDER Rocket Motor weighing 46 kg (100 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 2 kg (4 pounds) were added. Gross weight of the loaded container was 63 kg (137 pounds).

Due to unavailability only one container was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

In addition, due to their similarities in design, size and weight, this test is considered representative of qualification testing for the Mk 287 Mods 0, 1 (Drawing #1516486) and Mk 764 Mod 0 (Drawing #5972149) Shipping and Storage Containers as per the variation in Title 49 CFR 107, Sec. 178.601g(4), Variation 4.

## TESTS PERFORMED

### 1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

### 2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 1,057 kg (2,329 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

**3. Drop Test**

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom.
- b. Flat top.
- c. Flat on long side.
- d. Flat on short side.
- e. One corner.

**PASS/FAIL**

**1. Base Level Vibration Test**

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

**2. Stacking Test**

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

**3. Drop Test**

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

**TEST RESULTS****1. Base Level Vibration Test**

Satisfactory.

**2. Stacking Test**

Satisfactory.

**3. Drop Test**

Satisfactory.

Accession For	
NTIS	CRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
Unannounced <input type="checkbox"/>	
Justification _____	
By _____	
Distribution / _____	
Availability Codes	
Dist	Avail and/or Special
A-1	

**DISCUSSION****1. Base Level Vibration Test**

The input vibration frequency was 4 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

**2. Stacking Test**

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

**3. Drop Test**

After each drop, the container was inspected. The contents were completely retained by the container.

**REFERENCE MATERIAL**

A. Code of Federal Regulations, Title 49 CFR, Parts 107-178.

B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

**DISTRIBUTION LIST**

Defense Technical Information Center (2 copies)

ATTN: DTIC/FDA

Bldg. 5, Cameron Station  
Alexandria, VA 22304-6145

DLA Depot Operations Support Office

Bldg. 32F, DGSE

ATTN: Tom McElwee

Richmond, VA 23297-5000

Commander

Naval Surface Warfare Center

ATTN: Crane Division (Code 4053)

Crane, IN 47522-5000

## TEST DATA SHEET

<b>POP MARKING:</b>	
UN 4A1/Y63/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
Nomenclature: Mk 37 Mod 0 Shipping and Storage Container	
Type: 4A1	NSN: 8140-00-563-0205
Drawing Number or P/N: LD 269069	Outer Packaging Material: Steel
Dimensions: 77" L x 8.2" W x 6.75" H	Tested Gross Weight: 63 kg (137 pounds)
Closure (Method/Type): 5/8" strapping, removable cover	Tested Tare Weight: 15 kg (33 pounds)
Additional Description:	
<b>PACKAGED COMMODITY:</b>	
Name: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A      At 50 °C: N/A      At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount per Package: See table 1	Flash Point: N/A
Net Weight: See table 1	
<b>PACKAGED COMMODITY USED FOR TEST:</b>	
Name: Simulated SIDEWINDER Rocket Motor	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	Tested Net Weight: 48 kg (104 pounds)
Additional Description:	
The net weight includes the current maximum commodity weight plus an additional 2 kg (4 pounds).	

N/A = Not Applicable

**TABLE 1**  
**Commodities Approved for Shipping in the**  
**Mk 37 Mod 0 Shipping and Storage Container**

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
N/A	N/A	Mk 36 Mod 8	1331110	1.3C	0186	1	46 (100)	61 (133)
N/A	N/A	Mk 36 Mod 9	1331110	1.3C	0186	1	45 (99)	60 (132)
N/A	N/A	Mk 36 Mod 10	1331110	1.3C	0186	1	45 (99)	60 (132)
N/A	N/A	Mk 36 Mod 11	1331110	1.3C	0186	1	45 (99)	60 (132)

**Mk 287 Mods 0, 1 Shipping and Storage Container**

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
V380	1337-01-090-9294	Mk 36 Mod 8	1331110	1.3C	0186	1	46 (100)	61 (133)
V884	1337-01-131-7860	Mk 36 Mod 9	1331110	1.3C	0186	1	45 (99)	60 (132)
V887	1337-01-145-9360	Mk 36 Mod 10	1331110	1.3C	0186	1	45 (99)	60 (132)
V888	1337-01-145-1963	Mk 36 Mod 11	1331110	1.3C	0186	1	45 (99)	60 (132)

**Mk 764 Mod 0 Shipping and Storage Container**

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
VH09	1377-01-326-1359	Mk 112 Mod 1 RAM Rocket Motor	5972149	1.3C	0186	1	39 (86)	53 (116)

N/A = Not Assigned